

ES-52011H/ES-52012H/ES-52013H

2MP H.265 IP Camera



H.265



3D DNR



6KV Protection



DWDR




IP67

Features

- 2.0MP H.265 real-time coding
- 3D DNR, DWDR
- IR-Cut filter, Day&Night
- PoE power supply
- Lightning Protection up to 6KV
- IP67 ingress protection
- Support iOS/Android Phone/Pad, remote monitoring
- Video Linkage with Access Control System (BioSecurity 3.0)

Dimensions



Specifications

Model	ES-52011H	ES-52012H	ES-52013H
Camera			
Image Size	1920*1080		
Image Sensor	2.0MP 1/2.9" Progressive Scan CMOS		
Min. illumination	Color: 0.01Lux @ (F1.2,AGC ON); 0 Lux with IR B/W: 0.001Lux @ (F1.2,AGC ON); 0 Lux with IR		
Shutter Time	1/25s to 1/10,000s		
Lens	2.8mm	3.6mm	6mm
Lens Mount	M12		
Horizontal FOV	114°	78°	51°
Day & Night	IR-Cut filter with auto switch		
Digital NR	3D DNR		
IR Range	10-20m		
Image			
Resolution	1080P (1920*1080), 1.3MP (1280*960), 720P (1280 * 720P), D1, CIF		
Main Stream	1080P@25fps		
Sub Stream	704*576@25fps		
Third Stream	1280*720@25fps		
Image Settings	Saturation, Brightness and Contrast are adjustable through Web browser or Client software.		
Compression			
Video Compression	H.265/H.264		
Bite Rate	32Kbps~8Mbps		
Encode Mode	VBR/CBR		
Audio	G.711A/G.711Mu/G.726/G.726ASF		
Interface			
Ethernet	1*10/100Mbps RJ45 Ethernet port		
Audio I/O	N/A		
Network			
Network Storage	Support 802.1X		
Alarm Trigger	Motion Detection, Private Mask, Local Alarm, etc.		
Network Protocols	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP, SNMP		
Interface Protocol	ONVIF Profile S/API		
ROI	Support 4 fixed region for mainstream and sub stream separately		
Line Cross Detection	Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported		
General Function	Anti-flicker, Dual-stream, Image Capture, Password Protection		
General			
Temperature	-30 C ~ 60 C		
Humidity	10%-90% RH		
Power Supply	DC12V±10% 2A, PoE; Max. 3W		
Protection Level	IP67		
Weight	360g		
Dimensions	Φ102x93.2mm		

